


2009
CRF250R



***The CRF250R.
Why so many
trophy shelves
are overcrowded.***

CRF250R Winning is what the CRF®250R does best. Taking top honors in *TransworldMotocross* four times as "250 Four-Stroke MX Bike of the Year." All you have to do is take a look at the specs to know why. It's equipped with the advanced Honda Progressive Steering Damper™ to improve cornering ability. And it's powered by the race-proven Honda Unicam® four-stroke engine. Plus there's a bikeload of innovations inspired by Honda's race team. The CRF250R. It's not just a hot motocross bike. It's a trophy magnet.



Red

UNIQUE FEATURES

- Powerful four-stroke 249cc liquid-cooled single-cylinder four-valve Unicam[®] engine with lightweight titanium intake valves and magnesium ACG cover, clutch cover and cylinder-head cover.
- Forged 13.1:1-compression slipper piston and rings are lighter than a conventional design, revving quickly while maintaining excellent cylinder sealing and high-rpm power.
- Honda Progressive Steering Damper[™] (HPSD[™]). Tested by Team Honda, this lightweight, compact steering damper improves cornering ability and reduces rider fatigue.
- HRC works-type rear brake system integrates the rear master cylinder and fluid reservoir, eliminating the separate reservoir and hose.
- Dual-muffler exhaust system centralizes mass and reduces turning inertia.
- Twin-Spar aluminum frame with forged-aluminum steering head.

SPECIFICATIONS

Model	CRF250R	DIMENSIONS	
ENGINE		Wheelbase	58.2 inches
Engine	249cc liquid-cooled single-cylinder four-stroke	Seat Height	38 inches
Compression Ratio	12.9:1	Ground Clearance	14.2 inches
Valve Train	Unicam [®] , four-valve	Curb Weight*	227 pounds
Induction	Keihin [®] 40mm flat-slide carburetor		*Includes all standard equipment, required fluids and a full tank of fuel
Ignition	CD with electronic advance	Fuel Capacity	1.9 gallons
CHASSIS / SUSPENSION / BRAKES		DRIVETRAIN	
Front Suspension	47mm inverted Showa [®] ; 12.4-inch travel	Transmission	Close-ratio five-speed
Rear Suspension	Pro-Link [®] Showa single shock; 12.4-inch travel	FACTORY WARRANTY	
Front Brake	Single 240mm disc with twin-piston caliper	See dealer for details	
Rear Brake	Single 240mm disc		

ENVIRONMENTAL COMMITMENT

At Honda, we believe in performance and leadership, and that's why we're taking a leadership position when it comes to the environment. We continue to develop low-emission technologies for our current and future motorcycles, ATVs, scooters and personal watercraft. And that's the kind of performance everybody can appreciate.

DESIGNED EXCLUSIVELY FOR OFF-ROAD OPERATOR-ONLY USE IN ORGANIZED, CLOSED-COURSE RACING EVENTS. ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIVE CLOTHING WHENEVER YOU RIDE. NEVER RIDE UNDER THE INFLUENCE OF DRUGS OR ALCOHOL. USE COMMON SENSE, KEEP YOUR RIDING AREA CLEAN, RESPECT THE RIGHTS OF OTHERS WHEN YOU RIDE, AND NEVER MODIFY YOUR MOTORCYCLE'S SILENCER, EXHAUST SYSTEM OR SPARK ARRESTOR. Keihin[®] is a registered trademark of Keihin Mfg. Co., Ltd. Showa[®] is a registered trademark of Showa Mfg., Inc. CRF[®], Unicam[®], Pro-Link[®], Honda Progressive Steering Damper[™] and HPSD[™] are trademarks of Honda Motor Co., Ltd. ©2008 AHMC



IT'S A HONDA