



For further information on Scarabeo 50 Four Stroke and Scarabeo 100 Four Stroke, visit the website at www.apriliascarabeo.com where you can find details on all Scarabeo models. If you already own a Scarabeo, why not join the Scarabeo Club, details of which you will find on the home page. The Club is the perfect way of staying up to date with all the latest news and events in the fantastic world of Scarabeo.

100 Four Stroke (50 Four Stroke)

Engine	Horizontal single cylinder four stroke. Overhead cam. Forced air cooling. Catalytic exhaust.
Fuel	Lead free petrol.
Bore and stroke	50 x 49 mm (39.0 x 41.8 mm).
Displacement	96.2 cc (49.9 cc).
Compression ratio	10.5:1 (11.5-12:1).
Fuel system	Dell'Orto carburettor, Ø 22 mm (Keihin Ø 20 mm).
Ignition	Electronic.
Starting	Electric starter and kick-start.
Alternator	Permanent magnet, 12V - 120 W.
Lubrication	Forced wet sump lubrication with orbital pump.
Gearbox	Air cooled automatic variator.
Clutch	Automatic centrifugal.
Primary drive	V belt.
Final drive	Gearbox.
Frame	Single spar with double cradle in high strength steel.
Front suspension	Hydraulic fork. Wheel travel 80 mm.
Rear suspension	Hydraulic monoshock. Wheel travel 82 mm (80 mm).
Brakes	Front: 220 mm stainless steel disk. Calliper with two opposed 30 mm pistons. Rear: 140 mm drum.
Wheels	Light alloy, five petal-configuration spokes. Front 1.60 x 16". Rear 1.85 x 16".
Tyres	Front: 80/80 x 16". Rear: 90/80 x 16".
Dimensions	Max. length: 1,905 mm Max. width: 705 mm Max. height: 1,270 mm Seat height: 780 Wheelbase: 1,256 mm
Tank capacity	8 litres (including 1 litre reserve).
Accessories	<ul style="list-style-type: none"> • Complete large windshield • Single key top box with passenger backrest (50 Four Stroke) • Passenger footrests (50 Four Stroke) • Body Guard armoured cable lock • Leg cover

Euro2

Scarabeo 50/100 Quattrotempi is an ecological vehicle with communitarian homologation Euro2, in the respect of the acoustic and atmospheric pollution limits.