



M1000 SNO PRO 162"

ENGINE

Type	2-stroke
Displacement	999 cc
Cooling	Liquid
Cylinders	Twin
Bore x Stroke	90.3 x 78 mm
Lubrication	Oil Injection
Ignition	3D
Carburetion	50 mm throttle body batteryless EFI
Exhaust	APV™ with tuned pipe, pipe sensor and canister
Fuel Capacity	11.4 gal.

POWER TRAIN

Drive	Arctic (rpm sensing)
Driven clutch	Arctic (roller cam) ACT™ drive system
Brakes	Hydraulic disc

SUSPENSION

Front suspension	AWSTM VI double-wishbone A-arms with FOX Float® air shocks
Front travel	9.2 in.
Rear suspension	ACT™ M Series slide-rail, FOX® Zero Pro (IFP) shock on front arm, FOX Float® shock on rear arm
Rear travel	19 in.

DIMENSIONS

Overall length	132 in.
Overall width	46 in.
Ski stance	39-41 in. (adjustable)
Track width	15 in.
Track length	162 in.
Lug	2.25 in.

COLOR

White

STANDARD FEATURES

Dual halogen (4-bulb) headlight, UHMW plastic saddleless ski material, Digital/analog tachometer, Digital/analog speedometer, Dual stage trip odometer, Mechanical gas gauge, Low oil light, Coolant overheat light, Reverse, High/low hand warmer, High/low thumb warmer, Mountain strap, Spark plug holder, Belt holder, Deluxe Gauge, Telescoping handlebar

OPTIONAL FEATURES

Tether switch, Hitch, Mirrors, High windshield, Ice scratchers, Tank pads, Tunnel flares, Rack, Goggle holder, Storage bags, Tunnel deflectors

SUGGESTED RETAIL

TBA



©2009 Arctic Cat Inc. All rights reserved. ™ and the Arctic Cat logo are trademarks of Arctic Cat Inc. Because of our ongoing commitment to product quality and innovation, Arctic Cat reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. See your dealer for details.