



SNO PRO 500

ENGINE

Type	2-stroke
Displacement	499 cc
Cooling	Liquid
Cylinders	Twin
Bore x Stroke	71 x 63 mm
Lubrication	Oil injection
Ignition	3D
Carburetion	38 mm throttle body batteryless EFI
Exhaust	Tuned pipe and canister
Fuel Capacity	11 gal.

POWER TRAIN

Drive	Arctic (rpm sensing)
Driven clutch	Team driven
Brakes	Hydraulic disc

SUSPENSION

Front suspension	AWS™ VIII double-wishbone A-arms with FOX® Zero Pro IFP and sway bar
Front travel	9.5 in.
Rear suspension	Slide-action frame with coupling blocks, adjustable torsion springs and FOX® (IFP) shocks, 2" dia. rear shock
Rear travel	13.5 in.

DIMENSIONS

Overall length	117 in.
Overall width	49.5 in.
Ski stance	43 in.
Track width	15 in.
Track length	128 in.
Lug	1.25 in.

COLOR

Green

STANDARD FEATURES

Dual halogen (4-bulb) headlight, UHMW plastic saddleless ski material, Hand warmer, Thumb warmer, Mid-height windshield, Tether switch, Sway bar, Digital/analog tachometer, Digital/analog speedometer, Dual stage trip odometer, Electric fuel gauge, Low oil light, Coolant overheat light

OPTIONAL FEATURES

Low windshield, Spark plug holder, Sport bumper

SUGGESTED RETAIL

TBA



©2009 Arctic Cat Inc. All rights reserved. ™ and the Arctic Cat logo are trademarks of Arctic Cat Inc. Because of our ongoing commitment to product quality and innovation, Arctic Cat reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. See your dealer for details.