

EXPEDITION

2010 EXPEDITION® SE



PACKAGE HIGHLIGHTS

- Rotax® 1200 4-TEC® engine choice
- Rotax 600 H.O. SDI engine choice
- REV-XU™ platform
- Synchromesh transmission w/ reverse (2-1-N-R)
- Winch (680 kg / 1500 lb capacity)
- Hitch
- Skid plate and heavy-duty front bumper
- Heated GPS holder
- 12V power outlet
- Rack and cargo box (75 liters / 20 gal)
- 30 amp/hr heavy-duty battery
- Multi-function digital gauge w/display
- Additional rear 12V power outlet
- Modular two-up seat w/ underseat storage
- Adjustable heated passenger grips
- Handlebars with mountain strap, J-hooks and tilt steering
- Temperature gauge

ENGINE CHOICE COLOR CHOICE

Rotax 1200 4-TEC	Regal Red
Rotax 600 H.O. SDI	

ENGINE

Engine	Rotax 1200 4-TEC	Rotax 600 H.O. SDI
Engine details	Liquid-cooled, four-stroke D.O.H.C. dry sump	Liquid-cooled, e-R.A.V.E.™
Cylinders	3	2
Displacement	1170.7 cc / 46.9 in ³	594.4 cc / 36.3 in ³
Bore	91 mm / 3.6 in	72 mm / 2.8 in
Stroke	60 mm / 2.4 in	73 mm / 2.9 in
Max. engine speed	7800 RPM	8100 RPM
Carburetion	EFI	Electronic SDI
Fuel type	Regular unleaded recommended	Regular unleaded recommended
Min. octane	87	87
Fuel tank	45 liters / 12 gallons	45 liters / 12 gallons
Engine oil capacity	3.5 liters / 3.7 quarts	2.5 liters / 2.6 quarts
Exhaust system	Single head-pipe, baffle muffler	Single tuned-pipe, baffle muffler

POWERTRAIN

Drive clutch type	TRA™ IV	TRA III
Driven clutch type	QRS	QRS
Engagement	2500 RPM	3000 RPM
Drive sprocket number of teeth	8	8
Drive sprocket diameter	183 mm / 7.2 in	183 mm / 7.2 in
Brake system	Hydraulic	Hydraulic

SUSPENSION

Front suspension	Dual A-arm
Front shock	Hydraulic
Front suspension max. travel	210 mm / 8.26 in
Rear suspension	RCG-A
Center shock	Hydraulic
Rear shock	HPG™
Rear suspension max. travel	340 mm 13.4 in

DIMENSIONS

Vehicle overall length	3923 mm / 154.5 in
Vehicle overall width	1217 mm / 47.9 in
Vehicle overall height	1330 mm / 52.3 in
Official dry weight	332 kg / 732 lb (1200 4-TEC) 304 kg / 670 lb (600 H.O. SDI)
Ski stance	975 to 1018 mm / 38.4 to 40.1 in
Ski width	161 mm / 6.33 in
Track nominal width	500 mm / 20 in
Track nominal length	3968 mm / 156 in
Track profile height	31.8 mm / 1.25 in

FEATURES

Frame	REV -XU	Backrest	Standard	Speedometer	Standard	Mirrors	Standard
Skis	Pilot 6.9	Electric start	Standard	Tachometer	Standard	Windshield	High
Seating	2-Up modular w/ underseat storage	Reverse	Mechanical	Fuel gauge	Standard	Carbide runner	Standard
Handlebar	Tilt steering, 4 positions / Painted steel / J-hooks / Riser block (205 mm / 8 in) / Mountain strap	Heated throttle lever	Standard	Temperature gauge	Standard	Hitch	Tongue type
		Heated grips	Standard				

